A.Forster

according to Regulation (EC) No. 1907/2006

BPO-Härter rot

Version 1.1	GB/EN	Revision Date: 29.10.2019	Date of last issue: 05.04.2019 Date of first issue: 05.04.2019
SECTIO	N 1: Identific	ation of the substa	nce/mixture and of the company/undertaking
1.1 Produ	ıct identifier		
Trade	e name	: BPO-Ha	ärter rot
Prod	uct code	÷ 124.55 ²	I Hardener (124.632)
1.2 Relev	ant identified	uses of the substanc	e or mixture and uses advised against
	of the Sub- ce/Mixture	: Curing	chemical
1.3 Deta	ils of the sup	plier of the safety data	a sheet
Com	pany		
		info@fo	erster-co.de
Telep	ohone	: 04122-3	682
Resp	oonsible Depa	artment : Laborate	ory
		04122-3 info@fo	682 erster-co.de
1.4 Eme	rgency teleph	one number	
Telep	hone	: POISON Australia	IS INFORMATION CENTRE
		13 11 26	3
1.5 Detai	ils of the supp	olier/importer	
Com		Sydney Unit A3,	Automotive Paints and Equipment 366 Edgar Street Park, 2200
		receptio	n@sape.com.au
Telep Telefa	hone ax	÷ 02 9772 ∶ 02 9772	
Resp	oonsible Depa	artment : Marketir 02 9772	-



BPO-Härter rot

Version		Revision Date:	Date of last issue: 05.04.2019
1.1	GB/EN	29.10.2019	Date of first issue: 05.04.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Organic peroxides, Type E	H242: Heating may cause a fire.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Short-term (acute) aquatic hazard, Cate- gory 1	H400: Very toxic to aquatic life.
Long-term (chronic) aquatic hazard, Cat- egory 1	H410: Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

Warning

2

Hazard statements

H242 Heating may cause a fire.H317 May cause an allergic skin reaction.

- H319 Causes serious eye irritation.
- H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements : F

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.

Prevention:

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P220 Keep/Store away from clothing/ strong acids, bases, heavy metal salts and other reducing substances /combustible materials.
- P234 Keep only in original packaging.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
- P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if pre-



Version 1.1	GB/EN	Revision Date: 29.10.2019	Date of last issue: 05.04.2019 Date of first issue: 05.04.2019	

sent and easy to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P410 Protect from sunlight.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label: dibenzoyl peroxide

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Mixture contains Organic Peroxide

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
dibenzoyl peroxide	94-36-0 202-327-6 617-008-00-0 01-2119511472-50	Org. Perox. B; H241 Eye Irrit. 2; H319 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M factor (acute) = 10 M factor (chronic) = 10	>= 45 - < 55
ethanediol	107-21-1 203-473-3 603-027-00-1 01-2119456816-28	Acute Tox. 4; H302 STOT RE 2; H373	>= 1 - < 10

For explanation of abbreviations see section 16.



BPO-Härter rot

Version		Revision Date:	Date of last issue: 05.04.2019
1.1	GB/EN	29.10.2019	Date of first issue: 05.04.2019

SECTION 4: First aid measures

4.1 Description of first aid meas	ure	S
General advice	:	In the case of accident or if you feel unwell, seek medical ad- vice immediately. Move out of dangerous area. Take off contaminated clothing and shoes immediately. Show this safety data sheet to the doctor in attendance. First aider needs to protect himself.
If inhaled	:	Move to fresh air. Get medical attention.
In case of skin contact	:	Wash off immediately with soap and plenty of water. Call a physician if irritation persists.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses. Consult a physician.
If swallowed	:	Rinse mouth with water. Do NOT induce vomiting. Call a physician immediately.
4.2 Most important symptoms ar	nd e	effects, both acute and delayed
Risks	:	May cause an allergic skin reaction. Causes serious eye irritation.
4.3 Indication of any immediate	me	dical attention and special treatment needed
Treatment	:	Treat symptomatically.
Treatment SECTION 5: Firefighting meas	: sur	
	: sur	
SECTION 5: Firefighting meas	: sur :	
SECTION 5: Firefighting meas	: sur :	es Hazchem: 1W Carbon dioxide (CO2) Dry powder Water spray jet
SECTION 5: Firefighting meas 5.1 Extinguishing media Suitable extinguishing media Unsuitable extinguishing	:	es Hazchem: 1W Carbon dioxide (CO2) Dry powder Water spray jet Alcohol-resistant foam High volume water jet



BPO-Härter rot

Version 1.1	GB/EN	Revision 29.10.20		
Specia	e for firefighte al protective ec fighters		:	Wear self-contained breathing apparatus and protective suit.
Furthe	Further information		:	Use water spray to cool unopened containers. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions :	Wear personal protective equipment. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas. Remove all sources of ignition. Do not smoke. Avoid contact with skin, eyes and clothing. In the case of vapour formation use a respirator with an approved filter.
------------------------	--

6.2 Environmental precautions

Environmental precautions	:	Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages
		cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Do not flush with water.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures	:	Ensure that eyewash stations and safety showers are close to the workstation location.
Advice on safe handling	:	Use only with adequate ventilation. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Keep away from heat and sources of ignition. Handle and open container with care. Keep container tightly closed and dry. Never return unused material to storage receptacle.

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Ve 1.1	rsion	GB/EN	Revision [29.10.201		Date of last issue: 05.04.2019 Date of first issue: 05.04.2019			
				polymerisat Avoid inhala In case of ir equipment.	omposition. Itamination with readily oxidizable materials and ion accelerators. ation of vapour or mist. Insufficient ventilation, wear suitable respiratory se to the environment.			
Advice on protection against : fire and explosion			against :	Keep away ignition. Keep away Avoid shocl Take mease	Normal measures for preventive fire protection. Keep away from open flames, hot surfaces and sources of ignition. Keep away from direct sunlight. Avoid shock and friction. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment.			
7.2	2 Condit	tions for safe	storage, in	cluding any ir	ncompatibilities			
		rements for sto and containers		Avoid letting Keep conta Store betwe	ginal container. g the product become dry. iners tightly closed in a cool, well-ventilated place. een 5 and 25 °C in a dry, well ventilated place sources of heat, ignition and direct sunlight.			
	Advic	e on common s	storage :	Keep away Incompatibl	from food, drink and animal feedingstuffs. from reducing agents. e with acids and bases. al compounds			
	Recor perati	mmended stora	age tem- :	<= 25 °C				
7.3	Specif	ic end use(s)						
	•	fic use(s)	:	for ventilation ment etc. ca	ailable hich cover amongst other things the requirement on, protective clothing, personal protective equip- an be obtained from the National Occupational Safety Board.			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis			
dibenzoyl peroxide	94-36-0	TWA	5 mg/m3	GB EH40			
Further information	Where no specific short-term exposure limit is listed, a figure three times the						
	long-term exposure limit should be used.						
dimethyl phthalate	131-11-3 TWA 5 mg/m3 GB EH40						
	STEL 10 mg/m3 GB EH40						
ethanediol	107-21-1	STEL	40 ppm	2000/39/EC			

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Version 1.1	GB/EN	Revision Date: 29.10.2019	Date of last issue: 05.04.2019 Date of first issue: 05.04.2019	
			104 mg/m3	

			104 mg/m3			
Further information	Identifies the	oossibility of significa	ant uptake through the skin, I	ndicative		
		TWA	20 ppm	2000/39/EC		
			52 mg/m3			
Further information	Identifies the	possibility of signification	ant uptake through the skin, I	ndicative		
		TWA (Vapour)	20 ppm	GB EH40		
			52 mg/m3			
Further information	Can be absorbed through the skin. The assigned substances are those for					
	which there are concerns that dermal absorption will lead to systemic toxicity.					
		TWA (particles)	10 mg/m3	GB EH40		
Further information	Can be absor	bed through the skin	. The assigned substances a	re those for		
	which there ar	e concerns that deri	mal absorption will lead to sy	stemic toxicity.		
		STEL (Vapour)	40 ppm	GB EH40		
			104 mg/m3			
Further information	Can be absor	bed through the skin	. The assigned substances a	re those for		
	which there a	e concerns that der	mal absorption will lead to sy	stemic toxicity.		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	<u>,</u>		<u>, ,</u>	
Substance name	End Use	Exposure routes	Potential health ef- fects	Value
dibenzoyl peroxide	Consumers	Oral	Long-term systemic effects	2 mg/kg bw/day
	Workers	Dermal	Long-term systemic effects	13.3 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	39 mg/m3
ethanediol	Workers	Inhalation	Long-term local ef- fects	35 mg/m3
	Workers	Dermal	Long-term systemic effects	106 mg/kg
	Consumers	Inhalation	Long-term local ef- fects	7 mg/m3
	Consumers	Dermal	Long-term systemic effects	53 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dibenzoyl peroxide	Fresh water	0.00002 mg/l
	Intermittent use/release	0.000602 mg/l
	Marine water	0.000002 mg/l
	Fresh water sediment	0.0127 mg/kg dry weight (d.w.)
	Marine sediment	0.00127 mg/kg dry weight (d.w.)
	Soil	0.0025 mg/kg dry weight (d.w.)
	Sewage treatment plant	0.35 mg/l
ethanediol	Fresh water	10 mg/l
	Marine water	1 mg/l
	Sewage treatment plant	199.5 mg/l
	Fresh water sediment	37 mg/kg
	Marine sediment	3.7 mg/kg

Revision Date:



Date of last issue: 05.04.2019

BPO-Härter rot

Version

1.1	GB/EN	29.10.2019	
8.2 Expos	ure controls		
Perso	onal protective	equipment	
Eye p	protection	:	Safety glasses with side-shields conforming to EN166
	protection aterial	:	Neoprene gloves
Ma	aterial	:	Nitrile rubber
Br	eak through tim	e :	> 30 min
GI	ove thickness	:	>= 0.14 mm
Di	rective	:	DIN EN 374
Pr	otective index	:	Class 2
Re	emarks	:	Gloves should be discarded and replaced if there is any indi- cation of degradation or chemical breakthrough. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protec- tive glove. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
Skin a	and body protec	tion :	Please wear suitable protective clothing, e.g. made of cotton or heat-resistant synthetic fibres. Long sleeved clothing
Respi	iratory protection	n :	Apply technical measures to comply with the occupational exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
			In case of inadequate ventilation wear respiratory protection.
Filter	type	:	Combined particulates and organic vapour type (A-P)
Prote	ctive measures	:	When using do not eat, drink or smoke. Ensure that eye flushing systems and safety showers are located close to the working place. Avoid contact with the skin and the eyes. Use only with adequate ventilation.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties



BPO-Härter rot

Ver 1.1	sion GB/EN	Revision D 29.10.2019	te: Date of last issue: 05.04.2019 Date of first issue: 05.04.2019
	Appearance	:	paste
	Colour	:	red
	Odour	:	characteristic
	Melting point/range	:	not determined
	Boiling point/boiling r	ange :	not determined
	Flash point	:	Not applicable, Decomposition
	Upper explosion limit flammability limit	/ Upper :	not determined
	Lower explosion limit flammability limit	/Lower :	not determined
	Vapour pressure	:	not determined
	Density		1.15 - 1.25 g/cm3 (20 °C)
	Solubility(ies) Water solubility	:	insoluble
	Partition coefficient: r octanol/water	ì- :	No data available
	Viscosity Viscosity, kinemat	ic :	not determined
	Oxidizing properties	:	Organic peroxide
			Sustains combustion
9.2	Other information		
	Self-Accelerating dec tion temperature (SA		50 °C
	Peroxide content	:	50 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

:

10.3 Possibility of hazardous reactions

Hazardous reactions

Risk of decomposition.

Reacts violently in contact with acids, amines, driers, polymer-

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

 10.4 Conditions to avoid Conditions to avoid 10.5 Incompatible materials Materials to avoid 	: Do not Extrem Keep a Contac tion at	accelerators and easily oxidized materials. expose to temperatures above: > 25 °C es of temperature and direct sunlight. way from heat and sources of ignition. t with incompatible substances can cause decomposi- or below SADT.
Conditions to avoid 10.5 Incompatible materials Materials to avoid	Extrem Keep a Contac tion at	es of temperature and direct sunlight. way from heat and sources of ignition. t with incompatible substances can cause decomposi- or below SADT.
Materials to avoid		rators, strong acids and bases, heavy metals and
		rators, strong acids and bases, heavy metals and
		metal salts, reducing agents
0.6 Hazardous decomposition	products	
Irritant, caustic, flammable, n decomposition	noxious/toxic g	ases and vapours can develop in the case of fire and
11.1 Information on toxicologica Acute toxicity		
Not classified based on availand the second state of the second st	able informati	on.
dibenzoyl peroxide:		
dibenzoyl peroxide: Acute oral toxicity	: LD50 O	ral (Rat): > 2,000 mg/kg
	: LC0 (Ra	ral (Rat): > 2,000 mg/kg at): > 24.3 mg/l re time: 4 h
Acute oral toxicity	: LC0 (Ra	at): > 24.3 mg/l
Acute oral toxicity Acute inhalation toxicity	: LC0 (Ra Exposu : Acute to	at): > 24.3 mg/l
Acute oral toxicity Acute inhalation toxicity ethanediol:	 LC0 (Ra Exposu Acute to Method LC50 (F Exposu 	at): > 24.3 mg/l re time: 4 h oxicity estimate: 500.0 mg/kg

Serious eye damage/eye irritation

Causes serious eye irritation.



BPO-Härter rot

Version 1.1	GB/EN	Revision D 29.10.2019		Date of last issue: 05.04.2019 Date of first issue: 05.04.2019			
Resp	oiratory or ski	in sensitisatio	on				
-	sensitisation	i gic skin reactio	on.				
•	iratory sensi lassified base	tisation d on available	information.				
	n cell mutage lassified base	nicity d on available	information.				
	inogenicity lassified base	d on available	information.				
-	oductive toxi lassified base	city d on available	information.				
	STOT - single exposure Not classified based on available information.						
	STOT - repeated exposure Not classified based on available information.						
<u>Com</u>	ponents:						
ethar	nediol:						
Asse	ssment	:	May cause exposure.	damage to organs through prolonged or repeated			
-	ration toxicity	•					
Not c	lassified base	d on available	information.				
<u>Com</u>	ponents:						
ethar	nediol:						
No as	spiration toxici	ty classificatio	n				
SECTION	N 12: Ecolog	gical informa	tion				
12.1 Toxi	city						
Com	ponents:						
diber	nzoyl peroxid	le:					
Toxic	to fish	:	Exposure ti	orhynchus mykiss (rainbow trout)): 0.0602 mg/l me: 96 h ECD Test Guideline 203			
				X 0 0040 //			

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 0.11 mg/l aquatic invertebrates Exposure time: 48 h Method: OECD Test Guideline 202

NOEC (Fish): 0.0316 mg/l Exposure time: 96 h

according to Regulation (EC) No. 1907/2006



BPO-Härter rot

Vers 1.1	ion GB/EN	Revision [29.10.201		te: Date of last issue: 05.04.2019 Date of first issue: 05.04.2019
	Toxicity to algae	:		ErC50 (Pseudokirchneriella subcapitata (microalgae)): 0.0711 mg/l Exposure time: 72 h Method: OECD Test Guideline 201 NOEC (Pseudokirchneriella subcapitata (green algae)): 0.02
				mg/l Exposure time: 72 h
	M-Factor (Acute aqua icity)	atic tox- :		10
	Toxicity to daphnia a aquatic invertebrates ic toxicity)			EC10: 0.001 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211
	M-Factor (Chronic ac toxicity)	juatic :		10
	ethanediol:			
	Toxicity to fish	:		LC50 (Pimephales promelas (fathead minnow)): > 72,860 mg/l Exposure time: 96 h
	Toxicity to daphnia a aquatic invertebrates			EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
	Toxicity to algae	:		NOEC (algae): > 100 mg/l Exposure time: 72 h
	Toxicity to fish (Chroi icity)	nic tox- :		NOEC: 15,380 mg/l Exposure time: 28 d Species: Fish
	Toxicity to daphnia a aquatic invertebrates ic toxicity)			NOEC: >= 1,000 mg/l Exposure time: 23 d Species: Daphnia magna (Water flea)
	Persistence and de No data available	gradability	,	
	Bioaccumulative po No data available	otential		
	Mobility in soil No data available			
12.5	Results of PBT and	vPvB asse	es	sment
	Product:			



Version 1.1	GB/EN	Revision Date: 29.10.2019	Date of last issue: 05.04.2019 Date of first issue: 05.04.2019
Asse	ssment	to be e very p	ubstance/mixture contains no components considered either persistent, bioaccumulative and toxic (PBT), or ersistent and very bioaccumulative (vPvB) at levels of or higher
12.6 Othe	er adverse eff	ects	
<u>Prod</u> Addit matic	ional ecologic	al infor- : No dat	ta available
SECTIO	N 13: Dispos	sal considerations	
13.1 Was	te treatment	nethods	
Prod	uct	Do not	t mix waste streams during collection. t dispose of with domestic refuse.

	tainer at hazard	nto drains, dispose of this material and its con- lous or special waste collection point. ccordance with local regulations.
Contaminated packaging	the unused pro	is not properly emptied must be disposed of as duct. ccordance with local regulations.
Waste Code	16 05 06, labora hazardous subs icals	Vaste Codes are only suggestions: atory chemicals, consisting of or containing stances, including mixtures of laboratory chem- kides, for example hydrogen peroxide

SECTION 14: Transport information

14.1 UN number		
ADN	:	UN 3108
ADR	:	UN 3108
RID	:	UN 3108
IMDG	:	UN 3108
ΙΑΤΑ	:	UN 3108
14.2 UN proper shipping name		
ADN	:	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
ADR	:	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
RID	:	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)



BPO-Härter rot

Vers 1.1	sion	GB/EN	Revision [29.10.201	
	IMDG		:	ORGANIC PEROXIDE TYPE E, SOLID (dibenzoyl peroxide)
	IATA :		Organic peroxide type E, solid (dibenzoyl peroxide)	
14.3	3 Trans	port hazard c	lass(es)	
	ADN		:	5.2
	ADR		:	5.2
	RID		:	5.2
	IMDG		:	5.2
	ΙΑΤΑ		:	5.2
14.4	4 Packii	ng group		
		g group fication Code	:	Not assigned by regulation P1 5.2
	Classif Labels	ng group fication Code I restriction co	: : de :	Not assigned by regulation P1 5.2 (D)
	Classif	g group fication Code d Identification	: Number : :	Not assigned by regulation P1 539 5.2
	IMDG Packin Labels EmS C		:	Not assigned by regulation 5.2 F-J, S-R
	ΙΑΤΑ (Cargo) Ig instruction (570
		ig group	:	Not assigned by regulation Division 5.2 - Organic peroxides, Handling Label - Keep Away From Heat
		Passenger) ig instruction (craft)	passen- :	570
	Packin Labels	ig group	:	Not assigned by regulation Division 5.2 - Organic peroxides, Handling Label - Keep Away From Heat
14.5	5 Enviro	onmental haz	ards	
	ADN Enviro	nmentally haz	ardous :	no



Version 1.1	GB/EN	Revision 29.10.20		Date of last issue: 05.04.2019 Date of first issue: 05.04.2019	
AD Env	R ⁄ironmentally ha	azardous	: no		
RID Env	ironmentally ha	azardous	: no		
IME Mai)G rine pollutant		: yes		Hazchem: 1W
14.6 Sp	ecial precautio	ns for user			

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	:	Not applicable
REACH - List of substances subject to authorisation (Annex XIV)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EC) No 850/2004 on persistent organic pol- lutants	:	Not applicable
REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII)	:	Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P6b SELF-REACTIVE SUBSTANCES AND **MIXTURES and ORGANIC** PEROXIDES

E1

ENVIRONMENTAL HAZARDS

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.



Version		Revision Date:	Date of last issue: 05.04.2019
1.1	GB/EN	29.10.2019	Date of first issue: 05.04.2019

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

	:	Heating may cause a fire or explosion. Harmful if swallowed. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure. Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.
Full text of other abbreviation	ns	
Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Eye Irrit.	:	Eye irritation
Org. Perox.	:	Organic peroxides
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not



Version		Revision Date:	Date of last issue: 05.04.2019
1.1	GB/EN	29.10.2019	Date of first issue: 05.04.2019

Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the	mixture:	Classification procedure:		
Org. Perox. E	H242	Based on product data or assessment		
Eye Irrit. 2	H319	Calculation method		
Skin Sens. 1	H317	Calculation method		
Aquatic Acute 1	H400	Calculation method		
Aquatic Chronic 1	H410	Calculation method		

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.