according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Carsystem KS-550

Product code : 126.029

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Coatings

stance/Mixture

Recommended restrictions

on use

Professional use, Industrial use

1.3 Details of the supplier of the safety data sheet

Company : Vosschemie GmbH

Esinger Steinweg 50 25436 Uetersen

Germany

info@vosschemie.de

Telephone : 04122 717 0 Telefax : 04122 717158

Responsible Department : Laboratory

04122 717 0

sds@vosschemie.de

1.4 Emergency telephone number

Telephone : POISONS INFORMATION CENTRE

Australia

13 11 26

1.5 Details of the supplier/importer

Company : Sydney Automotive Paints and Equipment

Unit A3, 366 Edgar Street

Condell Park, 2200

reception@sape.com.au

Telephone : 02 9772 9000 Telefax : 02 9772 9001

Responsible Department : Marketing

02 9772 9000

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

Long-term (chronic) aquatic hazard, Cat-

H411: Toxic to aquatic life with long lasting effects.

H336: May cause drowsiness or dizziness.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

Buildup of explosive mixtures possible without

sufficient ventilation.

Precautionary statements : P101 If medical advice is needed, have product container or

label at hand.

P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open

flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

Storage:

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics acetone

Hydrocarbons, C9, Aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : aerosol Mixture

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 12.5 - < 20
isoalkanes, cyclics, <5% n-	921-024-6	Skin Irrit. 2; H315	
hexane	01-2119475514-35	STOT SE 3; H336	
		(Central nervous	
		system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	
		H411	
Hydrocarbons, C7-C9, n-alkanes,	Not Assigned	Flam. Liq. 2; H225	>= 10 - < 12.5
isoalkanes, cyclics	920-750-0	STOT SE 3; H336	
	01-2119473851-33	(Central nervous	
		system)	
		Asp. Tox. 1; H304	
		Aquatic Chronic 2;	

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

		H411	
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066	>= 10 - < 12.5
Hydrocarbons, C9, Aromatics	Not Assigned 918-668-5 01-2119455851-35	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411 EUH066	>= 1 - < 2.5

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : First aider needs to protect himself.

Remove from exposure, lie down.

If unconscious, place in recovery position and seek medical

advice.

Take off contaminated clothing and shoes immediately. Symptoms of poisoning may appear several hours later.

If inhaled : Move to fresh air.

If symptoms persist, call a physician.

In case of skin contact : Wash off immediately with soap and plenty of water.

If symptoms persist, call a physician.

In case of eye contact : In case of eye contact, remove contact lens and rinse imme-

diately with plenty of water, also under the eyelids, for at least

15 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Swallowing is not regarded as a possible method for expo-

sure.

Immediately give large quantities of water to drink.

Get medical attention immediately.

4.2 Most important symptoms and effects, both acute and delayed

Risks : Causes skin irritation.

Causes serious eye irritation. May cause drowsiness or dizziness.

according to Regulation (EC) No. 1907/2006



Hazchem: 2YE

Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Carbon dioxide (CO2)

Dry powder Water spray jet Alcohol-resistant foam

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

: Vapours may form explosive mixtures with air.

Build-up of dangerous/toxic fumes possible in cases of

fire/high temperature.

Hazardous combustion prod: :

ucts

Carbon monoxide, carbon dioxide and unburned hydrocar-

bons (smoke).

5.3 Advice for firefighters

Special protective equipment :

for firefighters

Use personal protective equipment. Wear suitable respiratory

protection equipment.

Further information : Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. Use water spray to cool unopened containers.

In the event of fire and/or explosion do not breathe fumes.

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Wear personal protective equipment.

Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Avoid inhalation of vapour or mist.

Avoid contact with skin, eyes and clothing.

6.2 Environmental precautions

Environmental precautions : Should not be released into the environment.

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Ventilate the area.

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For personal protection see section 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Local/Total ventilation : Ensure adequate ventilation.

Advice on safe handling : Pressurized container: Protect from sunlight and do not ex-

pose to temperatures exceeding 50°C / 122 °F. Also after use,

do not open with force or burn.

Provide sufficient air exchange and/or exhaust in work rooms.

Advice on protection against

fire and explosion

Do not spray on a naked flame or any incandescent material. Keep away from open flames, hot surfaces and sources of

ignition. Keep away from direct sunlight.

Hygiene measures : Do not inhale aerosol.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage

areas and containers

Please observe the storage instructions for aerosols! Keep containers tightly closed in a cool, well-ventilated place. Solvent vapours are heavier than air and may spread along floors. Keep away from direct sunlight. Keep away from heat

and sources of ignition.

Further information on stor-

age conditions

Storage must be in accordance with the BetrSichV (Germany).

Advice on common storage : Keep away from food and drink.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
acetone	67-64-1	TWA	500 ppm	2000/39/EC

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

			1,210 mg/m3	
	Further inform	nation: Indicative		
		TWA	500 ppm 1,210 mg/m3	GB EH40
		STEL	1,500 ppm 3,620 mg/m3	GB EH40
butane (containing < 0,1 % butadiene (203-450-8))	106-97-8	STEL	750 ppm 1,810 mg/m3	GB EH40
	Further information: Capable of causing cancer and/or heritable genetic dam-			
	age.			
		TWA	600 ppm 1,450 mg/m3	GB EH40
	Further inform age.	nation: Capable of ca	ausing cancer and/or heritable	e genetic dam-

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg
Hydrocarbons, C7- C9, n-alkanes, isoal- kanes, cyclics	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
	Workers	Skin contact	Long-term systemic effects	773 mg/kg
	Consumers	Inhalation	Long-term systemic effects	608 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	699 mg/kg
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Inhalation	Long-term local ef- fects	2420 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
	Consumers	Inhalation	Long-term systemic effects	200 mg/m3
	Consumers	Skin contact, Oral	Long-term systemic effects	62 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Sewage treatment plant	100 mg/l
Fresh water sediment	30.4 mg/kg
Marine sediment	3.04 mg/kg
Soil	29.5 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Safety glasses with side-shields conforming to EN166

Hand protection

Material: butyl-rubberBreak through time: > 480 minGlove thickness: >= 0.4 mmDirective: DIN EN 374Protective index: Class 6

Remarks : The choice of an appropriate glove does not only depend on

its material but also on other quality features and is different from one producer to the other. The exact break through time can be obtained from the protective glove producer and this

has to be observed. Preventive skin protection

Skin and body protection : Please wear suitable protective clothing, e.g. made of cotton

or heat-resistant synthetic fibres.

Long sleeved clothing

Respiratory protection : No personal respiratory protective equipment normally re-

quired.

In case of inadequate ventilation wear respiratory protection. When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Filter type : Filter type A-P

Protective measures : Use only with adequate ventilation.

When using do not eat, drink or smoke. Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist.

Environmental exposure controls

Soil : Avoid subsoil penetration.

Water : Do not flush into surface water or sanitary sewer system.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : black

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Odour : solvent-like

Melting point/freezing point : not determined

Initial boiling point and boiling

range

Not applicable

Upper explosion limit / Upper

flammability limit

10.9 %(V)

Lower explosion limit / Lower

flammability limit

0.6 %(V)

Flash point : Not applicable

Ignition temperature : > 200 °C

pH : not determined substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : not determined

Viscosity, kinematic : not determined

Solubility(ies)

Water solubility : immiscible

Partition coefficient: n-

octanol/water

not determined

Vapour pressure : 8 hPa (20 °C)

Density : 0.76 g/cm3 (20 °C)

9.2 Other information

Explosives : Not explosive

In use, may form flammable/explosive vapour-air mixture.

Self-ignition : not auto-flammable

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if used as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Revision Date: Date of last issue: 21.06.2021 Version 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

10.4 Conditions to avoid

Conditions to avoid Keep away from heat and sources of ignition.

Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : No data available

10.6 Hazardous decomposition products

Build-up of dangerous/toxic fumes possible in cases of fire/high temperature.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity LD50 Oral (Rat): > 5,840 mg/kg

Acute inhalation toxicity LC50 (Rat): > 25.2 mg/l

Exposure time: 4 h Test atmosphere: vapour

: LD50 Dermal (Rat): > 2,800 - 3,100 mg/kg Acute dermal toxicity

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

LD50 Oral (Rat): > 5,840 mg/kg Acute oral toxicity

Acute inhalation toxicity LC50 (Rat): > 23.3 mg/l

Exposure time: 4 h Test atmosphere: vapour

Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,800 - 3,100 mg/kg

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Acute inhalation toxicity : LC50 (Rat): ca. 132 mg/l

> Exposure time: 3 h Test atmosphere: vapour

: LD50 Dermal (Rabbit): > 7,426 mg/kg Acute dermal toxicity

Hydrocarbons, C9, Aromatics:

Acute oral toxicity : LD50 Oral (Rat, female): ca. 3,492 mg/kg

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Acute inhalation toxicity : LC50 (Rat): > 6.193 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,160 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Causes skin irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Result : Skin irritation

Hydrocarbons, C9, Aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

Hydrocarbons, C9, Aromatics:

Germ cell mutagenicity- As- : Classified based on benzene content < 0.1% (Regulation (EC)

sessment 1272/2008, Annex VI, Part 3, Note P)

Carcinogenicity

Not classified based on available information.

Components:

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Carcinogenicity - Assess- : Classified based on benzene content < 0.1% (Regulation (EC)

ment 1272/2008, Annex VI, Part 3, Note P)

Hydrocarbons, C9, Aromatics:

Carcinogenicity - Assess: Classified based on benzene content < 0.1% (Regulation (EC)

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

ment 1272/2008, Annex VI, Part 3, Note P)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9, Aromatics:

Assessment : May cause respiratory irritation., May cause drowsiness or

dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9, Aromatics:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

SECTION 12: Ecological information

12.1 Toxicity

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 15.8 mg/l

End point: mortality Exposure time: 72 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

End point: Biomass Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to microorganisms : EC50 (Bacteria): 35.57 mg/l

End point: Growth rate Exposure time: 48 h

Toxicity to fish (Chronic tox-

icity)

NOELR: 2,045 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 3 - 10 mg/l

End point: mortality Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 4.6 - 10 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Pseudokirchneriella subcapitata (green algae)): 10 - 30

mg/l

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

End point: Growth rate Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: 0.574 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOELR: 1 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

acetone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 8,120 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia pulex (Water flea)): 8,800 mg/l

End point: mortality Exposure time: 48 h

Toxicity to algae/aquatic

plants

NOEC (Microcystis aeruginosa (blue-green algae)): 430 mg/l

Exposure time: 96 h

Toxicity to microorganisms : EC10 (Bacteria): 1,000 mg/l

Exposure time: 0.5 h

Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chron-

ic toxicity)

NOEC: 2,212 mg/l Exposure time: 28 d

Species: Daphnia magna (Water flea) Method: OECD Test Guideline 211

Hydrocarbons, C9, Aromatics:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 9.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3.2 mg/l

End point: Immobilization Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOELR (Pseudokirchneriella subcapitata (green algae)): 1

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Toxicity to fish (Chronic tox-

icity)

NOELR: 1.228 mg/l Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other : aquatic invertebrates (Chron-

NOELR: 2.144 mg/l Exposure time: 21 d

ic toxicity) Species: Daphnia magna (Water flea)

12.2 Persistence and degradability

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics:

Biodegradability : Biodegradation: 98 %

Exposure time: 28 d

Method: OECD Test Guideline 301F

acetone:

Biodegradability : Biodegradation: 90.9 %

Exposure time: 28 d

Method: OECD Test Guideline 301B

Hydrocarbons, C9, Aromatics:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 78 % Exposure time: 28 d

Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Partition coefficient: n-

octanol/water

: No data available

acetone:

Bioaccumulation : Bioconcentration factor (BCF): 3

Partition coefficient: n-

octanol/water

log Pow: -0.24 (20 °C)

12.4 Mobility in soil

No data available

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : According to the European Waste Catalogue, Waste Codes

are not product specific, but application specific.

Dispose of in conjunction with appropriate waste disposal authorities and in accordance with disposal regulations.

Contaminated packaging : Dispose of in accordance with local regulations.

Waste Code : The following Waste Codes are only suggestions:

08 01 11, waste paint and varnish containing organic solvents

or other hazardous substances 150104, metallic packaging

15 01 10, packaging containing residues of or contaminated

by hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

IATA (Passenger)

Packing instruction (passen-

ger aircraft)

203

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation
Labels : Division 2.1 - Flammable gases

14.5 Environmental hazards

ADN

Environmentally hazardous : yes

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes Hazchem: 2YE

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mix-

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer

: Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of

explosives precursors

Acquisition, introduction, possession or use of the explosive precursor by the general public is subject to report-

acetone (ANNEX II)

ing obligations.

Seveso III: Directive 2012/18/EU of the Euro- P3a FLAMMABLE AEROSOLS

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021
1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

pean Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

E2 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2004/42/EC

Volatile organic compounds (VOC) content: < 840 g/l VOC content for the product in a ready to use condition.

15.2 Chemical safety assessment

A chemical safety assessment according to (EC) regulation 1907/2006 (REACH) has not been carried out for this product.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.

H226 : Flammable liquid and vapour.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Liq. : Flammable liquids
Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits

2000/39/EC / TWA : Limit Value - eight hours

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP -

according to Regulation (EC) No. 1907/2006



Carsystem KS-550

Version Revision Date: Date of last issue: 21.06.2021 1.2 GB / EN 23.07.2021 Date of first issue: 01.10.2019

Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL -International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS -Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Calculation method
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Aquatic Chronic 2	H411	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.