



Auto Refinishing Products

Page 1/18

Printing date: 28.07.2023

Revision date: 28.07.2023

Version no. 1

Safety Data Sheet
according to WHS Regulations

Hazardous according to criteria of Australian Safety and Compensation Council.

1 Identification

· **Product identifier**

· Trade name: **C499 CLEAR HS SR 2:1**

· Article number: 11362

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture

Coating compound/ Surface coating/ paint

Surface protection

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 & MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

· **Further information obtainable from:**

Sydney Automotive Paints & Equipment PTY LTD

Unit A3, 366 Edgar St. Condell Park NSW 2200

AUSTRALIA, Tel. +02 9772 9000 , +02 9772 9001

Continue on page 2
AU

Trade name: C499 CLEAR HS SR 2:1

- Emergency telephone number:
If poisoning occurs contact a doctor or Poisons Information Centre. Phone Australia 131 126, New Zealand 0800 764 766.

2 Hazard(s) Identification

Classification of the substance or mixture



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS02 GHS07

- Signal word Warning
- Hazard-determining components of labelling:
n-butyl acetate (30-<35 %)
- Hazard statements
H226 Flammable liquid and vapour.
H336 May cause drowsiness or dizziness.
- Precautionary statements
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P241 Use explosion-proof electrical/ventilating/lighting equipment.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures

- Description: Mixture of hazardous substances listed below with nonhazardous additions.

Dangerous components:

CAS: 123-86-4	n-butyl acetate	30-<35%
EINECS: 204-658-1	 Flam. Liq. 3, H226	
Index number: 607-025-00-1	 STOT SE 3, H336	
RTECS: AF 7350000		

Trade name: C499 CLEAR HS SR 2:1

CAS: 108-65-6	2-methoxy-1-methylethyl acetate	10-<15%
EINECS: 203-603-9	⚠ Flam. Liq. 3, H226	
Index number: 607-195-00-7		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	1-<5%
EINECS: 265-199-0	⚠ Flam. Liq. 3, H226	
Index number: 649-356-00-4	⚠ Asp. Tox. 1, H304	
	⚠ Acute Tox. 4, H332; STOT SE 3, H335	
CAS: 112-07-2	2-butoxyethyl acetate	1-<5%
EINECS: 203-933-3	⚠ Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
Index number: 607-038-00-2	Flam. Liq. 4, H227	
RTECS: KJ 8925000		
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≥0.1-<0.9%
EINECS: 255-437-1	⚠ Skin Sens. 1, H317	
Additional information: For the wording of the listed hazard phrases refer to section 16.		

4 First Aid Measures

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed
No further relevant information available.

5 Fire Fighting Measures

- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- **Special protective equipment and fire fighting procedures:** No special measures required.
- **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental Release Measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.

Trade name: **C499 CLEAR HS SR 2:1**

See Section 13 for disposal information.

* **7 Handling and Storage**

· **Handling:**

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· **Storage:**

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

* **8 Exposure controls and personal protection**

· **Additional information about design of technical facilities:** No further data; see section 7.

· **Ingredients with limit values that require monitoring at the workplace:**

123-86-4 n-butyl acetate

WES Short-term value: 950 mg/m³, 200 ppm
Long-term value: 713 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WES Short-term value: 548 mg/m³, 100 ppm
Long-term value: 274 mg/m³, 50 ppm
Sk

112-07-2 2-butoxyethyl acetate

WES Short-term value: 333 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Sk

· Additional information: The lists valid during the making were used as basis.

· **Personal protective equipment:**

· General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Continue on page 5

AU

Trade name: C499 CLEAR HS SR 2:1· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)**· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Tightly sealed goggles

· **Body protection: Protective work clothing****9 Physical and Chemical Properties**· **General Information**· **Appearance:**· **Form:**

Fluid

· **Colour:**

According to product specification

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value:**

Mixture is non-soluble (in water).

· **Change in condition**· **Melting point/freezing point:**

Undetermined.

· **Initial boiling point and boiling range:**

124-128 °C

· **Flash point:**

23 - 60 °C

· **Flammability (solid, gas):**

Flammable.

· **Autoignition temperature:**

315 °C

· **Decomposition temperature:**

Not determined.

· **Ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Risk of explosion by shock, friction, fire or other sources of ignition.

· **Explosion limits:**· **Lower:**

1.2 Vol %

· **Upper:**

10.8 Vol %

· **Vapour pressure at 20 °C:**

10.7 hPa

· **Density at 20 °C:**

0.89232 g/cm³

· **Relative density**

Not determined.

· **Vapour density**

Not determined.

· **Evaporation rate**

Not determined.

· **Solubility in / Miscibility with**· **water:**

Fully miscible.

· **Partition coefficient: n-octanol/water:**

Not determined.

· **Viscosity:**· **Dynamic:**

Not determined.

· **Kinematic:**

Not determined.

Continue on page 6

AU

Trade name: C499 CLEAR HS SR 2:1

- **Solvent content:**
- Organic solvents: 49.7 %
- VOC (EC) 443.5 g/l
- Solids content (volume): 50.2 %
- **Other information** No further relevant information available.

10 Stability and Reactivity

- **Reactivity** No further relevant information available.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological Information

- **Information on toxicological effects**
- Acute toxicity Based on available data, the classification criteria are not met.
- LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 123.077 mg/kg (rat)
Dermal LD50 81.026 mg/kg
Inhalative LC50/4 h >176 mg/l

123-86-4 n-butyl acetate

Oral LD50 13,100 mg/kg (rat)
Dermal LD50 >5,000 mg/kg (rabbit)
Inhalative LC50/4 h >21 mg/l (rat)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)
Inhalative LC50/4 h 35.7 mg/l (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)
Dermal LD50 >3,400 mg/kg (rab)
Inhalative LC50/4 h >10.2 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral LD50 2,400 mg/kg (rat)
Dermal LD50 1,580 mg/kg (rabbit)
Inhalative LC50/4 h 11 mg/l (ATE)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** May cause drowsiness or dizziness.

Trade name: **C499 CLEAR HS SR 2:1**

- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.

* 12 Ecological Information

· **Toxicity**

· Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· **Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· **Behaviour in environmental systems:**

· Bioaccumulative potential No further relevant information available.

· Mobility in soil No further relevant information available.

· **Additional ecological information:**

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· **Results of PBT and vPvB assessment**

· PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· vPvB: This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).

· **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

· **Waste treatment methods**

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· Recommendation: Disposal must be made according to official regulations.

· Recommended cleansing agents: Water, if necessary together with cleansing agents.

* 14 Transport information

· **UN-Number**

· ADG, IMDG, IATA UN1263

· **UN proper shipping name**

· ADG UN1263 PAINT

· IMDG, IATA PAINT

· **Transport hazard class(es)**

· ADG



· Class 3 (F1) Flammable liquids.

Trade name: C499 CLEAR HS SR 2:1

- Label 3
- IMDG, IATA



- Class 3 Flammable liquids.
- Label 3
- **Packing group**
- ADG, IMDG, IATA III
- **Environmental hazards:**
- Marine pollutant: No
- **Special precautions for user** Warning: Flammable liquids.
- Hazard identification number (Kemler code): 30
- EMS Number: F-E, S-E
- Stowage Category A
- **Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.
- **Transport/Additional information:**
- ADG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- Transport category 3
- Tunnel restriction code D/E
- IMDG
- Limited quantities (LQ) 5L
- Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
- **UN "Model Regulation":** UN 1263 PAINT, 3, III

* **15 Regulatory information**

·3Y

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

· Australian Inventory of Industrial Chemicals

- 123-86-4 n-butyl acetate
- 108-65-6 2-methoxy-1-methylethyl acetate
- 64742-95-6 Solvent naphtha (petroleum), light arom.
- 112-07-2 2-butoxyethyl acetate
- 1330-20-7 xylene
- 104810-47-1 mix of: a-3-(3-(2H-benzotriazol-2-yl)-5-t-butyl-4-hydroxyphenyl)propionyl-o-hydroxypoly(oxyethylene); a-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyl-o-3-(3-(2H-benzotriazol-2-yl)-5-tert-butyl-4-hydroxyphenyl)propionyloxypoly(oxyethylene)
- 41556-26-7 bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate

Continue on page 9
AU

Trade name: C499 CLEAR HS SR 2:1

68937-54-2 Siloxanes and silicones, di-Me, 3-hydroxypropyl-Me, ethoxylated

82919-37-7 methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate

77-58-7 dibutyltin dilaurate

· Standard for the Uniform Scheduling of Medicines and Poisons

1330-20-7 xylene: S6

· Australia: Priority Existing Chemicals

None of the ingredients is listed.

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



GHS02 GHS07

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate (30-<35 %)

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

· Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

* **16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

Trade name: C499 CLEAR HS SR 2:1

· **Department issuing SDS:** Department of Quality Control

· **Contact:**

HB BODY S.A

Ms Olympia Stamkou

Ph: +30 2310 790 032

fax: +30 2310 790 033

email: stamkou@hbbody.com

· * Data compared to the previous version altered.

AU
Continue on page 11

Trade name: C499 CLEAR HS SR 2:1

* **Annex: Exposure scenario 1**

· **Short title of the exposure scenario**

· **Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category PC9a** Coatings and paints, thinners, paint removers

· **Process category PROC8a** Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Article category AC1** Vehicles

· **Environmental release category ERC2** Formulation into mixture

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Used amount per time or activity** Smaller than 100 g per application.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** Use only on hard ground.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid long-term or repeated skin contact.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Trade name: C499 CLEAR HS SR 2:1

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

· **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Trade name: C499 CLEAR HS SR 2:1

Annex: Exposure scenario 2

Short title of the exposure scenario

Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

Conditions of use According to directions for use.

Duration and frequency Frequency of use:

Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture Raw material.

Other operational conditions

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Other operational conditions affecting consumer exposure Keep out of the reach of children.

Other operational conditions affecting consumer exposure during the use of the product Not applicable.

Risk management measures

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

No special measures required.

Provide explosion-proof electrical equipment.

Personal protective measures

Do not inhale gases / fumes / aerosols.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

Disposal measures Ensure that waste is collected and contained.

Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

Exposure estimation

Consumer

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

Trade name: C499 CLEAR HS SR 2:1

Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

AU
Continue on page 15

Trade name: C499 CLEAR HS SR 2:1

* **Annex: Exposure scenario 3**

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

Continue on page 16

AU

Trade name: C499 CLEAR HS SR 2:1

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

AU
Continue on page 17

Trade name: C499 CLEAR HS SR 2:1

* **Annex: Exposure scenario 4**

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** Raw material.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

No special measures required.

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

Continue on page 18

AU

Trade name: C499 CLEAR HS SR 2:1

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

AU